



H	H	x 2048	MJPEG
rue WDR	dB	WiseStrea	TZ x
P66 / K10			GB
R15m			

1/1.8	6M CMOS	RJ-45 (10/100BASE-T)
3,096x2,094		H.265/H.264/MJPEG
2,048x2,048		048x2048,1280x1280,1080x1080,960x960
		x , 20x 20,640x640,480x480
	0.1 Lux(F1.6 RE)	048x512,1920x 480,1280x 320,640x 160, 04x 6
	B/W : 0 Lux (R LED)	8x1024,1920x 960,1280x 640,640x 320, 04x 352
S/N	50dB	8x1536,1600x 1200,1280x 960,1024x 68
(CVBS 1.0Vp-p	x 600,640x 480, 04x 6
	WiFi	Q1/ 4x 8,800x 600,640x 480
		H.264/H. 0fps@2,048x2,04 MJPEG 15fps
		5ea /WiseStream
	1.6mm	H.264/H.
	F1.6	MJPEG :
	H : 192 / V : 192 / D : 192	H.265/H. BR VBR MJPEG VBR
	0.3m	10
	/	/ /
	(2.5VD 4mA 2
		(3.5) : 1Vrms
R	15m	G. -law/G.
/	85	G. (ADPCM) 8KHz G. 11 8KHz
R	/ / / /	G. : 16Kbps Kbps 32Kbps 40Kbps
/ BLC /HLC/ WDR		AAC-LC : 16KHz 8/16/32/48Kbps
120dB		P Pv4 Pv6
SSDR (/)		TCP/ P, UDP/ P, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP,
SSNR D+3D /		HTTP, HTTPS, SSL/TLS,DHCP, PPPoE, FTP, SMTP, CMP,
/ /		GMP, SNMPv1/v2c/v3(M B-2), ARP, DNS, DDNS,QoS,
/ (P M-SM, UPnP, Bonjour, S P
ATW/AWC/ / / (&		HTTPS SSL
/ / (2 1/12,000		P
8 TZ()		802.1 (EAP-TLS, EAP-LEAP)
/		/
&		20
/ /		SD/SDHC/SDXC 2 (512 GB),NAS
		C (
1/		A ONV F Profile S/G SUNAP (HTTP AP) Open platform
		Web (1
		Web Viewer : Windows / 8.1 / 1 MAC10. 0.12
		hrom MS Edge4 Mozilla Firefox55
		E1 Apple Safari1 Mac
FTP		SmartViewer SSM
		/ -40° C +55° C (-40° F +131° F)/RH90%
		/ -50° C +60° C (-58° F +140° F)/RH90%
		P6 K10
		/ DC12V± PoE (EEE802.3af 3)
		12W(DC12V) 12.95W(PoE)
		/ /
		146mm x H65.8mm
		q

